



Our flying allows us to watch the world from the air. We enjoy the feeling, which can have only birds. We bring you the amazing taste of movement in the air, ideal control of your flight and a perfect experience. Make the decision. Trust your instinct.

Trust your
Instinct

NIRVANA[®]
PARAMOTORS

TECH SPECS

Type	NS 200
Engine	Simonini MINI 2 Plus, NIRVANA Tuning
Power	27 HP (@ 6,800 rpm)
Ignition	NIRVANA CIR (electronic with pre-ignition and battery charging regulation, microprocessor controlled start/stop button, moto-hour recorder and rpm meter output)
Carburettor	Diaphragm WALBRO WG8
Reduction	Belting 1:2.4 NIRVANA
Exhaust	Tuned NIRVANA
Propeller	Carbon two-blade foldable 130 cm with central bolt
Starting Gear	Manual and electrical
Fuel Tank	14 litres, integrated
Body	Self-supporting laminated shell - carbon/Kevlar sandwich
Frame	Aluminium, five-parts reinforced NAP frame, aerodynamic carbon laminated struts, easy and fully dismantle
Harness	Anatomic construction absorbing remaining vibrations, straps AustiAlpin Cobra, underneath container - foldaway and easy to remove
Accessories	Maintenance-free NiCd battery, charged during the flight, socket 16.8 VDC, fuel gauger
Equipment	Padded bag for engine complete with wheels, propeller packs
Weight	23 kg (empty unit without harness)
Recommended Pilot Weight	80-160 kg (single or tandem)
Minimum Static Thrust	70 kP
Average fuel consumption	3-3.5 litres per hour (influenced by the type of canopy used and the pilot weight)

RECOMMENDED EQUIPMENT



Rescue Chute RS35



Small Wind Sock with Telescopic Pole



AGAMA Water Rescue System



FULL CONTACT 3 Helmet with Communication



PPG Boots Airstyle



Tactel RX-2 Flying Suit



FCR Flying Overall



Neoprene Hood



Carry Bag Flystyle

DO YOU KNOW OUR NEW SYSTEMS?



NIRVANA SYSTEMS s.r.o.
 Jatecni 523 • 760 01 Zlin
 Czech Republic
 Tel.: +420 577 226 616
 Fax: +420 577 019 117
 Email: info@nirvana.cz
www.nirvana.cz